spirit.

technical data.

home 40 clcf

click
plank: 1210 × 176,6 mm – box: 8 planks (=1,709 m2) – Pallet: 80 boxes (=136,76 m2)
tile: 914 × 610 mm – box: 4 tiles (=2,23 m2) – Pallet: 54 boxes (=120,43 m2)

product specifications.

		click comfort 40	
		plank	**tile**
Total thickness	EN ISO 24346	4 mm + 1 mm	4,5 mm + 1 mm
Thickness of the wear layer	EN ISO 24340	0,4	0,4
Total weight	EN ISO 23997	7,9 kg/m2	9,3 kg/m2
Usage classification	EN ISO 10582	23/32	23/32

test results.

Underfloor heating	EN ISO 12524	suitable – max. 27°C (80°F)/ electrical floor heating systams: max 60 W/m²	
Castor chair	EN ISO 4918	pass	pass
Fire resistance	EN ISO 13501–1	Bfl-s1	Bfl-s1
Light fastness	EN ISO 105-B02	> 7	> 7
Thermal resistance	EN 8302	0,035 m² K/W	0,035 m² K/W
Chemical resistance	EN ISO 26987	OK	OK
Residual indentation	EN ISO 24343–1	<0,1mm	<0,1mm
Slip resistance	DIN 51130	R10	R10
	EN ISO 13893	class DS	class DS
Sound reduction: impact sound	EN ISO 717–2	20 dB	20 dB
Reflected walking sound	EPLF draft 021029–3–2004	33 SONE (57% sound reduction)	33 SONE (57% sound reduction)
Dimensional stability	EN ISO 23999	< 0,15 %	< 0,15 %
Residential warranty		20 y	20 y
Commercial warranty		5 y	5 y
Formaldehyde	EN ISO 717–1	E1	E1
Lock strength	EN ISO 10582	> 4 kN/m	> 4 kN/m

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

4 bevels

23 32

EN 14041 CE 18 DOP: 454-CB3118-1 BerryAlloc NV Industrielaan 100 8930 Menen, Belgium NB: 0534 Resilient floor covering for use within building

Phthalate Free


INDOOR AIR COMFORT eurofins GOLD CERTIFIED PRODUCT

spirit.

home 40 clcf

Underlay

Material		IXPE
Thickness		1 mm
Compressive strength	EN 826	117 kPa
Punctual conformability	CEN TS 16354: 12-2013	0.52mm
Water absorption	EN 12087	0.6%













home 40 clcf

spirit.



1. Protective PU lacquer
2. Wear layer 0,4 mm
3. Decorative printfilm
4. Rigid board
5. Integrated underfloor (1 mm)

Total thickness: 4+1 mm (planks)
Total thickness: 4.5+1 mm (tiles)